

This manual is a simple setup manual for 2D barcode scanner. Detailed user manual can be downloaded from the official website or obtained from local dealer.

Настройки

1. Заводские настройки



Note: scan the "Recall default" settings code, all settings of barcode scanner will be restored to factory default settings.

With "*" marked below is default settings.

2. Интерфейс



Версия прошивки



USB Keyboard



USB COM (Virtual serial port)

3. Конец строки



* Add "Enter"



Remove "Enter"



Add newline



* Remove newline

4. Регистр



* Default case setting



All lowercase



All uppercase

5. Сигналы



* Вкл



Выкл

6. Настройки вывода (в USB HID)

The default is English, other languages can be set.



* Default



For Microsoft Excel & Notepad

The keyboard mode support output other languages by scanning the corresponding configuration code. (The default is English, other languages can be input)



For Microsoft Word

7. Язык



* USA



Spain



Italy



Singapore



Salvador



Japan



Thailand



Belgium



Sierra Leone



Turkey



Russia "windows1251"



Russian "Shift-jis"



Hungary



Germany



Algeria & Arabic



Spanish Latin



British



France



FULL ASCII

8. Чтение URL

2D handheld barcode scanner default enable.



Читать url QR code



Не читать url QR code

2D desktop barcode scanner default disable.

9. Notice

① Scanner cannot be activated.

Check whether the cable is firmly connected (there will be a crisp sound after the USB cable is connected to the device) and then check whether the USB is properly connected to the device. If it is not powered on, it can be changed to the USB port behind the host.

② Data is not uploaded

Check whether the USB cable is successfully connected to the computer. If it is connected correctly, there will be a prompt sound. The driver installation will appear when connecting to the computer for the first time. After the driver is automatically installed, scan the code to test whether there is a decoding prompt sound.

If the decoding is normal, please scan the USB Keyboard in this Setup manual.

If there is no response after scanning the code, please scan "Recall default" and then plug it in again.

If there is no response after re-powering, or no response after scanning the setting code, please contact the dealer's for technical support.

10. Тестовый штрих-код

Please use the scanner after the device has finished booting to prevent the device from being unable to recognize the scanner or causing the device to start abnormally. (You can try re-plug the device to solve this problem)

The following is the test barcode, which is used for transmission test.



12345678
2D barcode test



3 1 2 3 4 5 6 7 8 9 0 1 9
1D barcode test